

SE-1/SE-3

Single/Three-channel ECG

EDAN

Technical Specifications

	SE-1 Single Channel ECG	SE-3 Three-Channel ECG
Input Circuit	Defibrillator protection built-in	
Lead	Standard 12 leads	
Acquisition Mode	Single lead	12 leads simultaneously
A/D Converter	12 bits	12 bits / 24 bits (optional DE12 ECG board)
Measurement Range	± 5mVpp	
Time Constant	> 3.2s	
Frequency Response	0.05Hz ~ 150Hz (-3dB)	
Calibration Voltage	1mV ± 3%	
Sensitivity	2.5, 5, 10, 20 (mm/mV)	
Input Impedance	> 50MΩ	> 50MΩ
Input Circuit Current	<0.05μ A	
Noise Level	<15 μVp-p	
Baseline Adjustment	Automatic	
Patient Leakage Current	< 10 μ A (220V~240V)	
Patient Auxiliary Current	<0.1 μ A (DC)	
Filter	EMG Filter 35Hz (-3dB) AC Filter 50 Hz/60Hz (-20dB)	EMG Filter 25Hz/35Hz/45Hz /OFF DFT Filter 0.05/0.15/0.25/0.5Hz 0.32/0.67 Hz (optional DE12 ECG board) Lowpass Filter 150Hz/100Hz/75Hz AC Filter 50 Hz/60Hz
CMRR	≥110dB	≥110dB / ≥115dB (optional DE12 ECG board)
Recording Mode	Auto: 1CH, 1CH+1R Manual: 1CH	Auto: 3CH, 3/2 CH, 3CH+1R, 1CH, 1CH+1R Manual: 3CH, 3/2 CH, 1CH Rhythm: Single rhythm lead
Rhythm Lead	Any lead selectable	
Power Supply	AC: 100V~115V/220V~240V, 50/60Hz Built-in rechargeable Li-ion battery: voltage=14.8V More than 3 hrs continuous recording under battery supply	
Recorder	Thermal printer	
Record Paper	50mm x 30m	80mm x 20m
Paper Speed	25mm/s, 50mm/s (± 3%)	5mm/s, 6.25mm/s, 10mm/s, 12.5mm/s, 25mm/s 50mm/s (± 3%)
Dimension	288mm x 210mm x 70mm	
Weight	2.3kg	2.5kg
Display	192 x 64 pixels LCD	320 x 240 pixels LCD (Wide Screen) 192 x 64 pixels LCD (Narrow Screen)
External Input/Output	Input: > 100 kΩ ; Sensitivity 10mm/V ± 5% Output: < 100 Ω ; Sensitivity 1V/mV ± 5%	
Communication Interface	N/A	Ethernet, RS232



SE-1/SE-3

Single/Three-channel ECG



Edan Instruments, Inc.

3F-B, Nanshan Medical Equipments Park, Nanhai Rd 1019#, Shekou, Nanshan, Shenzhen, 518067 P.R. China
Tel: 86-755-2689 8326 Fax: 86-755-2689 8330 www.edan.com.cn Email: info@edan.com.cn



ENG-ECG-SE1&SE3-V1.2-20100414

All rights reserved.
Features and Specifications are subject to change without notice




SE-3 Three - Channel ECG



SE-3(Wide Screen)

- Foldable LCD screen, vivid waveform display
- 12 leads simultaneous acquisition
- Built-in high-resolution thermal printer
- Built-in rechargeable Li-ion battery, AC/DC power supply
- Automatic ECG measurement and interpretation

Smart ECG Viewer





PC-based ECG data management software

- Complete digital filtering, resisting baseline drift, AC and EMG interference
- Automatic baseline adjustment
- Auto/manual work mode
- Lead-off detection and alert
- Three printing formats (Auto, manual and rhythm) selectable
- Heart rate variability (HRV) analysis



SE-3(Narrow Screen)

- 12 leads printing by external ink-jet printer
- Large patient data storage: 120 ECGs (Narrow Screen) 144 ECGs (Wide Screen)
- PC-based ECG data management software (option)
- Easy data storage and transfer with USB flashdisk



SE-1 Single Channel ECG

- Foldable LCD screen, vivid waveform display
- Built-in high-resolution thermal printer
- Built-in rechargeable Li-ion battery, AC/DC power supply
- Well designed membrane keyboard

- Digital filtering, resisting baseline drift, AC and EMG interference
- Automatic baseline adjustment
- Auto/manual work mode
- Lead-off detection and alert