

DESIGN: LUXO



IP20



The right light

**LUXO**

8505-8506


# LHH LED

A highly flexible self balancing arm in conjunction with excellent light output has given our LHH diagnostic luminaires their vast popularity among the medical profession. The new LED version offers benefits over traditional halogen lamps. The frictionless horizontal and vertical movement and the ease of use make the LHH the most flexible examination luminaire on the market – and the best in its class.



The powerful LED light source provides 15,000 Lux at 1 metre, and has an expected life span of 40,000 hours. The energy consumption is less than half of a traditional halogen examination lamp. Modern lens optics provide a focused pool of light without annoying shadows. There is hardly any downward heat radiation.

LHH LED is available for table, trolley, wall or ceiling mounting. We offer a wide selection of specialized brackets for most mounting purposes.



## RELATED PRODUCTS



LHH table & trolley  
8505



LHH wall & ceiling  
8506

## 8505-8506 LHH LED

## OPTIONS

## LHH LED CEILING

Article no.	Light source	Watt	Total Effect	Weight	Angle	LED colour temp	Arm length	Colour rendering	Colours
8506-702-32	LED	15	18	2.2	10	4300	1040	93	<input type="checkbox"/>

## LHH LED TABLE

Article no.	Light source	Watt	Total Effect	Weight	Angle	LED colour temp	Arm length	Colour rendering	Colours
8505-702	LED	15	18	2.2	10	4300	1040	93	<input type="checkbox"/>

## LHH LED TROLLEY

Article no.	Light source	Watt	Total Effect	Weight	Angle	LED colour temp	Arm length	Colour rendering	Colours
8505-702-33	LED	15	18	2.2	10	4300	1040	93	<input type="checkbox"/>

## LHH LED WALL

Article no.	Light source	Watt	Total Effect	Weight	Angle	LED colour temp	Arm length	Colour rendering	Colours
8506-702	LED	15	18	2.2	10	4300	1040	93	<input type="checkbox"/>

## LIGHT DATA

Article no.	Watt	Total effect	Voltage	Work dist.	Lux	Colour temp.	Colour rendering	Life	Angle
8505-702	15 W	18 W	110-240 V	1.00 m	15 000	3700 K	93	40000	10
8505-702-33	15 W	18 W	110-240 V	1.00 m	15 000	3700 K	93	40000	10
8506-702	15 W	18 W	110-240 V	1.00 m	15 000	3700 K	93	40000	10
8506-702-32	15 W	18 W	110-240 V	1.00 m	15 000	3700 K	93	40000	10

## ACCESSORIES

Trolley, white	8990-037-1
SP bracket	8990-001-1
AH table clamp, white	8990-010-1
TE table bushing	8990-014-0
BSP brack etw/back plate	8990-023-1
Ceiling Mount 600 mm	8990-032-1
Ceiling Mount 1000 mm	8990-033-1
Ceiling Mount 1400 mm	8990-034-1
Ceiling Mount 600 mm, with socket	8990-029-1
Ceiling Mount 1000 mm, with socket	8990-030-1
Ceiling Mount 1400 mm, with socket	8990-026-1

## DESIGNATION

